



نام محصول : دوربین تحت شبکه IP Camera

نوع محصول : بولت Bullet

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : SR-5450C-T(6mm)

#### KEY FEATURE

- Metal Housing
- 256 × 192 resolution, 12 μm, Vox
- Temperature exception alarm for fire prevention
- 15°C to 550°C ,Max. (± 2°C, ± 2%)
- Max resolution 2880x1620
- Smart IR,IR Range:50m
- Built-In Mic,Built-In Speaker
- Support tripwire and perimeter
- Operating Conditions -40°C~65°C,0~95% RH
- DC12V,POE
- IP67

#### Camera

Image Sensor	1/2.7"CMOS
Min. Illumination	Color:0.002Lux@(F1.6,AGC ON),B/W:0Lux with IR
Shutter Time	1s-1/100000s
Day & Night	IR-cut filter with auto switch (ICR)
WDR	120dB
S/N	>39dB
Angle Adjustment	0-360°;0-90°;0-360°

#### Lens

Lens Type	Fixed
Focal Length	Thermal:7mm;Optical:6mm
Lens Mount	M12
Aperture Range	Thermal:F1.2;Optical:F1.6;Fixed
Field of View	Thermal:26°;Optical:53.8°(H);Thermal:20°;Optical:29.3°(V);Thermal:32.8°;Optical:61.3°(D)
DORI Distance	Detect:120m Observe:47.6m Recognize:24m Identify:12m

#### Illuminator

IR LEDs	2
IR Distance	50m
Wavelength	850nm
White LEDs	2
White light Distance	15m

#### Compression Standard

Video Compression	S+265/H.265/H.264B/H.264M/H.264H/Motion JPEG
Video Bit Rate	32k-16Mbps
Audio Compression	G.711A/G.711U/ADPCM_D/AAC_LC
Audio Sampling Rate	8kHz/32kHz/48kHz

#### Image

Max. Resolution	Optical: 2880x1620@30fps Thermal: 1280x720@25fps
Main Stream	Optical: PAL:25fps(2880x1620,2688x1520,2560x1440,2304x1296) NTSC:30fps(2880x1620,2688x1520,2560x1440,2304x1296) Thermal: PAL:25fps(1280x720,704x576,640x480,352x288) NTSC:25fps(1280x720,704x480,640x480,352x240)
Sub Stream	Optical: PAL:25fps(704x576,704x288,640x360,352x288) NTSC:30fps(704x480,704x240,640x360,352x240) Thermal:



	PAL:25fps(704x576,640x480,352x288) PAL:25fps(704x480,640x480,352x240)
Third Stream	N/A
BLC	Yes
HLC	Yes
AGC	Yes
3D DNR	Yes
White Balance	Auto/Semi-auto/Manual/Sunny/Natural light/Warm light/Sodium lamp/Incandescent lamp/Locked white balance
ROI	8 regions
Corridor mode	N/A
EIS	N/A
OSD	5regions;16*16/32*32/48*48/64*64/96*96
Picture Overlay	1 region
Privacy Mask	4 regions
Defog	Yes

#### Feature

Alarm Trigger	Motion Detection; Mask Alarm; Voltage Alarm; Disk Full; Disk R/W Error; IP Address Conflict; MAC Address Conflict; FTP Server Exception ; Event Input, Event Output
Linkage Method	send email; trigger sound; trigger warmlight; trigger recording; trigger capture; notify surveillance center
Video Analytics	Human/Vehicle Classification; Tripwire; Double Tripwire; Perimeter; Video Abnormal; Audio Abnormal
Rules of behavior analyse in 1 scene	8
Early Warning(EW)	N/A
Auto-Tracking	N/A
Face Mode	N/A
Face Detection Performance	N/A

#### Network

ANR	ANR
Protocols	HTTP;HTTPS;TCP/IP;UDP;UPnP;ICMP;IGMP;SNMP;DHCP;DNS;DDNS;Easy DDNS; NTP; SMTP; SSL;802.1X;QoS;IPv4;IPv6;PPPOE;SSH;Unicast;Multicast;RTCP;ARP;SRTP;RTSP;FTP;SFTP;NAS
System Compatibility	onvif Profile S/T/G/M;CGI;MIL STONE;RTMP
Remote Connection	≤2
Client	Easy7 Smart Client
Moblie Client	EasyLive Plus
Web	IE10+;Firefox52+;Edge89+;Safari11+;Chrome57+

#### Interface

Communication Interface	1 RJ45 10M/ 100M self adaptive Ethernet port
Audio I/O	1channel in;1channel out
Alarm I/O	2channel in,3mA,3.3VDC;1channel out,1A,24VDC
Built-In Mic	Yes
Built-In Speaker	Yes
Reset Button	Yes
On-board storage	Built-in Micro SD card slot, up to 512 GB
Additional interfaces	1 channel RS-485

#### General

Operating Temperature	-40°C-65°C
Operating Humidity	0-95%
Storage Temperature	-40°C-65°C
Storage Humidity	0-95%(non-condensing)
Power Supply	DC12V±25%,MAX 7W;POE 802.3af,MAX 8W
Protection	Surge protection 2000V;Lightning proof 6000V;IP67
Boundary Dimensions	327(L)114(W)105(H)mm
Package Dimensions	360(L)150(W)170(H)mm
GrossWeight	1.8kg
NetWeight	1.5kg



