



نام محصول : دوربین تحت شبکه IP Camera

نوع محصول : باکس Box

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : SR-5455B

KEY FEACTURE

- 1/1.8" CMO ;
- Min. Illumination : color : 0.0002Lux (AGC ON @F1.6) 、 B/W : 0.0001Lux (AGC ON @F1.6) ;
- Three Stream, Mainstream max resolution 3072x1728@25fps (PAL) ;
- Video Analytics : Running、Loitering、Heatmap、Crowed、People Counting (Vertical、Tripwire、Perimeter、Queue) 、Video detection、Double Tripwire、Parking、Object Lost、Object Abandon、Defocus detection、Audio Abnormal、On duty Detection ;
- Audio 1/1, Alarm I/O 2/2, RS485、RTC、TF card (Max 512G、Reset ;
- Protocols : IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, SSL, QoS, RTMP;
- CGI、GAT1400、Onvif Profile G/S/T、RTSP、Alicloud Protocol ;
- Intelligent monitoring, face capture dual-mode switching;
- Face Capture: Age、Gender、Mask、Glasses ;
- Number of single-screen face detection and capture: 32, 16;
- DC12V±25%/POE
- Operating Conditions : -35°C~65°C, Humidity less than 95% (non-condensing)

Camera

Image Sensor	1/1.8"CMOS
Resolution	5MP
Image resolution	Main stream max resolution: 5mp (3072x1728) Sub Stream max resolution: 4CIF (704x576) Third Stream max resolution:1080 (1920x1080)
Main Stream	PAL: 25fps (3072x1728, 2560x1440, 2304x1296) 50fps (1920x1080, 1280x720) NTSC: 30fps (3072x1728, 2560x1440, 2304x1296) 60fps (1920x1080, 1280x720)
Sub stream	PAL: 25fps (704x576, 640x360, 704x288, 352x288) NTSC: 30fps (704x576, 640x360, 704x240, 352x240)
Third stream	PAL: 25fps (1920x1080, 1280x720, 704x576, 704x288, 352x288) NTSC: 30fps (1920x1080, 1280x720, 704x576, 704x480, 704x240, 352x240)
Main Stream default bit rate	2Mbps
WDR	120 dB
Shutter Time	1-1/1000000S
Min. illumination	Color : 0.0002 lux (AGC ON @F1.6) W/D: 0.0001 lux (AGC ON @F1.6)
Image	3DDNR, AGC, White balance , BLC, Day & night, electronic image stabilization, digital zoom , electronic shutter, ROI, Video mirroring, HLC, Smart defog, OSD, privacy obscuration, Corridor mode (need to reboot)

Lens

Type c/cs

Connection

Remote connection ≤6

Interface

Communication Interface 1 RJ45 100M Self adaptive Ethernet port
Protocol CGL, GAT1400, RTSP, Onvif profile S/T/G/M
Exit Type External wiring
Other Audio1/1, alarm I/O 2/2, RS485 , RTC, TF card (max512G) , Reset

Compression Standard

Video Compression S+265, H265, H264 Baseline Profile / Main Profile / High Profile
Audio Compression G.711A, G711U, ADPCM_D, AAC_LC
Audio bit rate 8kHz, 4kHz, 48kHz
Video bit rate 32K-8Mbps
Audio noise reduction yes

Feature

Web Version Web 6.0

