



نام محصول : دستگاه سوئیچ شبکه PoE

نوع محصول : Switch

سازنده : شرکت فناوری نوین مرصاد فاطر

مدل : SRS-04G03G02F-P

## KEY FEATURES

4 Gigabit RJ45 POE Port	120 Watt
3 Gigabit RJ45 Uplink Port	18.2Gb Internal Bandwidth
2 Gigabit SFP Uplink Port	IC+ Processor
1 (Female)Fast RJ45 Uplink Port	PoE Distance up to 120m
	Metal Case

## interface

Total Port	10 Ports
Max POE Output	120Watt
POE Port Control	808AR
Fast RJ45 POE Port	N/A
Gigabit RJ45 POE Port	4 Port
Fast RJ45 Uplink Port	N/A
Gigabit RJ45 Uplink Port	3
Gigabit SFP Uplink Port	2
Combo Uplink Port	N/A
Power Transmit RJ45 Port	1 (Female)
Fast RJ45 Uplink Port	

## Network Performance

Standard	IEEE802.3x, IEEE802.3u, IEEE802.3az, IEEE802.3ab, IEEE802.3af, IEEE802.3at (Up to 30Watt), IEEE802.3bt
Protocols	CSMA/CD
Router	N/A
Speed	Ethernet 10Mbps (half duplex), 20Mbps (full duplex); 10BASE-T: 14,880bps/port Fast Ethernet 100Mbps (half duplex), 200Mbps (full duplex); 100BASE-TX:14,880bps/port Gigabit Ethernet 1000Mbps (half duplex), 2000Mbps (full duplex); 1000BASE-TX: 1488000bps/port
Cabling	10Base-TX:Cat 3 or above Cat.5 UTP(100m) POE=200M 100Base-TX:Cat 5 UTP(100m) POE=150M 1000Base-TX:Cat 6e UTP or Cat 6 UTP(120m) POE=150M
Bandwidth	18.2Gb Internal Bandwidth
MAC Table	64Kb
Auto MDI-MDIX	Yes All Port
Web	Yes – Lite Management (Non-CLI)

## Hardware

Processore Type	IC+
LED Panel	Data Activity, PoE Activity
Main Board	Double Layer
Case	Metal Case
Mounting	Rackmount / desktop
Security	Port Security, Access IP List, SSH & HTTPS Login, IEE 802.1 X MAB (MAC Authentication Bypass) / Radius Server Authentication

## PD'S

IP Camera	Yes
IP Phone	Yes
(+)5/4,(-)8/7	Optional
(+)2/1,(-)6/3	Yes



### General

IP Rating	IP51
Web Language	English
Dimension	250*105*45 mm
Weight	625 g
Storage Temp	-20°C ~ +70°C / 10% ~ 90% RH
Operation Temp	-15°C ~ +60°C / 10% ~ 90% RH
Radiation Electromagnetic	EN55016

### Status

	Ethernet Interfaces
LED	1000 LNK/ACT (Green), 10/100 LNK/ACT (Green) PoE Ethernet Interfaces, PoE-in-Use (af/at) 1000 LNK/ACT (Orange), 10/100 LNK/ACT (Green)

### Power Supply

Power	200~240V AC, 50~60Hz
Redundant	N/A
LED Power	Yes
Power Cable	Available

### Guarantee

Product Guarantee	3 Year Platinum Guarantee
MTBF	100K hrs min. MIL-HDBK-217F (25°)

